

OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI/CAN Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on April 14, 2021.

SealGuard Inc. - a subsidiary of Sub-Technical Inc. 363 Mars Valencia Road P.O. Box 1178 Mars, PA 16046 724-625-0008

Facility: Malcom, IA

Joining and Sealing Materials

Water Contact Contact
Trade Designation
Size
Temp
Material

Grouts

[2]

CLD 23 PUR

- [1] Minimum cure time is 2 hours at 65°F.
- [2] Certified for a maximum of 1% of the surface area of a 9,000 gallon tank or 0.03 sq. in./L.

Facility: Pine Grove, PA

Joining and Sealing Materials

| | | Water Water Contact Contact |
|------------------------|-----|--------------------------------|
| | | |
| [1] | | |
| Grouts | | |
| Hyperflex STI-03-0.15S | [2] | CLD 23 PUR |

- [1] Minimum cure time is 2 hours at 65°F.
- [2] Certified for a maximum of 1% of the surface area of a 9000 gallon tank or 0.03 sq. in./L.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International. 1 of 1