

# HyperFlex

Single Component, Closed Cell, Pre-Polymeric Sealant and Adhesive

## Applications

For use with less aggressive low flowing water leaks. Hyperflex is a flexible hydrophobic foam with excellent sealing and adhesion qualities that make it perfect for ground and water control applications.

## Advantages

- Non-shrink formulation
- Pre-blended catalyst: no on-site mixing
- 20:1 expansion ratio
- Great Migration Into Fractures
- Moisture activated
- NSF-61 approval for potable water

## Storage

Maintain seal until ready for application.

Avoid contact with moisture.

Store under 80°F 27°C.

**Product has a 2-year shelf life in unopened containers.**

## Packaging

10 oz (300 ml) Tube

5 gallon pails

55 Gallon Drums

## Transport

US D.O.T. Unregulated Class-55

## Customer Support

724-625-4550

info@SealGuardInc.com



## Uncured Physical Properties

Shrinkage (-20° F)	0% 1 Day	ASTM D-2126
Viscosity (68° F)	375 cps	
Specific Gravity (60° F)	1.18	
Percent Solids	100%	
Color	Amber	
Solvents	None	

## Cured Material - Physical Properties

Free Rise		Confined		
Density	2 PCF	Density	50 PCF	N/A
Compressive	125 psi	Compressive	3500 psi	ASTM D-1622
Tensile	75 psi	Tensile	3600 psi	ASTM D-1621
Shear	50 psi	Shear	1760 psi	ASTM D-638
Elongation	40%	Elongation	9%	ASTM D-3574

**\*\* Thoroughly read all instructions and cautions prior to use \*\***

